

ELECTRIC STACKER

CDD15K/CDD20K
CTD15K/CTD20K



CTDK

CDDK

Specification	1	Model		CDD15K/CDD20K
	2	Operating Type		Stand on
	3	Power Type		Electric
	4	Load Capacity	kg	1500/2000
	5	Load Center	c(mm)	600
	6	Wheel Type		Polyurethane
	7	Wheelbase	y(mm)	1330
	8	Wheel Size,front	mm	Φ 250×75
	9	Wheel Size,rear	mm	Φ 80×70
	10	Additional wheel	mm	Φ 115×50
	11	Thread,rear	b11(mm)	570/685
Dimensions	12	Lowered Mast Height	h1(mm)	2085/1765/2015/2165/ 2330/2000/2170/2340
	13	Max.lifting Height	h3(mm)	1600/2500/3000/3300/ 3500/4500/5000/5500
	14	Extended Mast Height	h4(mm)	2085/3050/3550/3850/ 3950/5050/5550/6050
	15	Lowered Fork Height	h13(mm)	90/95
	16	Overall Length	l1(mm)	2050
	17	Overall Width	b1(mm)	790
	18	Fork Dimensions	S/e/l(mm)	60/170/1150
	19	Width over Forks	b5(mm)	570/685
	20	Aisle Width, with Pallet 1000x1200 Crosswise	Ast(mm)	2455
	21	Aisle Width, with Pallet 800x1200 Lengthwise	Ast(mm)	2430
	22	Groud Clearance	m2(mm)	30
	23	Turning Radius	wa (mm)	1600
Performance	24	Speed	Lifting (Laden/unladen)	m/s
	25		Falling(Laden/unladen)	m/s
	26	Max.Gradeability	(Laden/unladen)	%
	27	Service Weight (include battery)		kg
Driven	28	Service brake		Electromagnetic -regenerative
	29	Motor	Driven Motor	kw
	30		Lift Motor	kw
	31		Steering Type	
	32	Battery	Voltage /noinal Capacity	V/Ah
	33		Size(L×W×H)	mm

